

MARISOLV® 9010 is a solvent /diluent for use with MARISEAL® SYSTEM liquid-applied waterproofing <u>1</u> membranes.

## Product Information

- One component, solvent/diluent
- Packaging
- 1lt/5lt/20lt metal pails
- Color
- Transparent

## Advantages

- Excellent compatibility with single component polyurethane liquid-applied waterproofing membranes and coatings
- Excellent solubility
- Suitable for use both for hand and airless
- spray application





# MARISOLV® 9010

#### Uses

MARISOLV® 9010 is used as a solvent / diluent. MARISOLV® 9010 is used in combination with MARISEAL® 250/260/270/etc. liquid-applied waterproofing membranes

### Application

Add MARISOLV<sup>®</sup> 9010 into MARISEAL<sup>®</sup> 250/260/270/etc. liquid-applied waterproofing membrane, and mix with a low-speed electrical mixer, for 2-3min, at a ratio of 4 to 8% by weight. For detailed application instructions, contact our technical department



Safety measures

MARISOLV® 9010 contains methyl ethyl ketone. Flammable. See information supplied by the manufacturer. Please study the Safety Data Sheet. PROFESSIONAL USE ONLY

Our technical advice for use, whether verbal or written, is given in good faith and reflect the current level of knowledge and experience with our products. When using our products, a detailed object-related and qualified inspection is required in each individual case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We may guarantee only that our products are compliant with their technical specification; correct application of our products therefore falls entirely within your scope of liability and Users are responsible, in any case, for complying with local legislation and for obtaining any required approvals or authorizations, when necessary, either for their purchase and/or for their use. Values in this technical data sheet are given as examples and may not be regarded as specifications. For product specifications contact our technical department. The new edition of the technical data sheet supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practice

## MARIS POLYMERS S.M.S.A.

Industrial Area of Inofita • 320 11 Inofita • Greece Tel: +30 22620 32918-9 marispolymers@saint-gobain.com • www.marispolymers.com