

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/20111
amended by Commissions delegated Regulation (EU) No 574/2014 **No PU 40**

No. PU 40

1. Unique identification code of the product-type: **MARIFLEX PU 40**
2. Intended use : **SEALANT FOR FACADE ELEMENTS: EN-15651-1: F-EXT-INT-CC. SEALANT FOR PEDESTRIAN WALKWAYS: EN-15651-4 F-EXT-INT-CC.**
3. Manufacturer (Distributor): **MARIS POLYMERS S.M.S.A.
Industrial Area of Inofita
GR-32011 Inofita
Grèce**
4. Authorised representative : **Not relevant**
5. System of assessment and verification of constancy of performance : **System 3, System 3 for reaction to fire
Reaction to fire test (Notified Body 370)
Notified Body (1292)**
6. Harmonised standard : **EN 15651-1 / EN 15651-4**

7. Declared performances:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	E	EN 15651-1 / EN 15651-4
Resistance to flow	≤ 3 mm	
Loss of Volume	≤ 10 %	
Tensile Properties after immersion in water	No Failure	
Tensile Properties	> 0.4	
Tensile properties for non-structural sealants used in cold climates	>0.6	
Tensile Properties at maintained extension	No Failure	
Tensile Properties at maintained extension -Cold climate	No Failure	
Tensile Properties after immersion in salt water	No Failure	
Tear resistance	No Failure	
Durability	Pass	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



MARIS POLYMERS S.M.S.A.
POLYURETHANE SYSTEMS
IND. AREA INO FYTA VIOTIA
32011 GREECE
TEL: +30 22620 32518-19 FAX: 22620 32040
VAT No. EL. 999528243

Inofyta, 17/07/2023
Kostas Varelas
Innovation, Development and Quality Manager

Inofyta, 17/07/2023
Thomas Ciffreo
Managing Director