

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/20111
amended by Commissions delegated Regulation (EU) No 574/2014

No.009

1. Unique identification code of the product-type: **MARISEAL 400W**
2. Intended use: Surface protection product for concrete – coating
Principles 2 Moisture Control - method 2.2
Principles 8 Increasing Resistivity – method 8.2
- Used in system with MARISEAL 710W,
MARISEAL 250W
3. Manufacturer: **MARIS POLYMERS S.M.S.A.**
Industrial Area of Inofita
GR-32011 Inofita
Greece
4. Authorised representative: Not relevant
5. System of assessment and verification of constancy of performance: **System 2+**
6. Harmonised standard: **EN 1504-2: 2004, ZA1.d**
Products and systems for the protection and repair of concrete structures. Definitions, requirements, quality control and evaluation of conformity. Part 2: Surface protection system for concrete
- Notified body:
Certificate of conformity of factory production control: **EUROCERT / 1128**
1128-CPR-10.09.0282

7. Declared performances:

Performance determined in system (MARISEAL 710W, MARISEAL 250W, MARISEAL 400W)

Essential characteristics	Performance	Test standard	Harmonized technical specification
Linear shrinkage	NPD	EN 12617-1	EN 1504-2: 2004
Coefficient of thermal expansion	NPD	EN 1770	
Adhesion by cross-cut test	NPD	EN ISO 2409	
Permeability to CO2	NPD	EN 1062-6	
Water vapour permeability	Class I: sD ≤ 5m	EN ISO 7783	
Capillary absorption and permeability to water	$\omega < 0,1 \text{ kg/m}^2 \cdot \text{h} \cdot 0,5$	EN 1062-3	
Thermal compatibility	NPD	EN 13687-1,2,3	
Resistance to thermal shock	NPD	EN 13687-5	
Chemical resistance	NPD	EN ISO 2812-1	
Crack bridging ability	NPD	EN 1062-7	
Adhesion strength by pull-off test	$\geq 1,5 (1,0) \text{ N/mm}^2$	EN 1542	
Reaction to fire	Class F	EN 13501-1	
Slip / skid resistance	NPD	EN 13036-4	
Behaviour after artificial weathering	NPD	EN 1062-11	
Antistatic behaviour	NPD	EN 1081	
Adhesion on wet concrete	NPD	EN 13578	
Dangerous substances	According 5.3	-	

Note: ¹⁾ The value in brackets is the lowest accepted value of any reading

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



MARIS POLYMERS S.M.S.A.
POLYURETHANE SYSTEMS
IND. AREA INOFYTA VIOTIA
52011 GREECE
TEL: +30 22620 32958-19 FAX: 22620 32040
VAT No. EL 999528243

Inofyta, 14/03/2023
Kostas Varelas
Innovation, Development & Quality Manager

Inofyta, 14/03/2023
Thomas Ciffreo
Managing Director